

OMNIKEY® 6221 USB Reader

Portable USB reader/memory stick with MicroSD™ slot

- ▶ **Enabling Mobile Document Security** – Ideal device for organizations needing to issue or transport secure content.
- ▶ **Cost Effective** – removable MicroSD™ memory of up to 32GB gives users the flexibility to increase the memory size as needed.
- ▶ **Fast Transmission** – Supports contact smart cards up to 420 Kbps and USB high speed interface supports transmission of up to 480 Mbps.



ACCESS quality.

The dongle sized OMNIKEY® 6221 is a portable and innovative reader/memory stick with MicroSD™ slot and reader for SIM-sized contact smart cards all in one device. Combining a smart card reader and memory means that data contained and carried on the OMNIKEY 6221 can easily be encrypted making it inaccessible to unauthorized personnel or in case the reader is lost or stolen.

The OMNIKEY 6221 introduces data protection and secure content issuance based on encryption and digital signature in conjunction with PIN protection. The reader offers convenient two-factor authentication which is particularly important and valuable to the increasingly mobile workforce.

The combination of a high-speed smart card reader with MicroSD™ capability is an industry first and the OMNIKEY 6221 USB reader enables a wide range of applications including data protection, log-on and secure content issuance. It is the ideal solution for organisations that value mobile document security, plan to use a secure and state-of-the art IT infrastructure and/or need to issue content tied to licenses such as software.

As part of the HID Global family of products the OMNIKEY 6221 reader provides an unparalleled card read support and compatibility.

Key benefits are:

- ▶ **Future Proof Investment** - The removable SIM-sized SAM module gives organisations the ability to re-use the reader by simply issuing a new SIM-sized SAM module.
- ▶ **Secure content issuing through SAM-based license** – Licenses tied to the SAM module cannot be duplicated therefore eliminating the potential of copying and redistributing data.
- ▶ **Innovative and Robust Design**– Small and lightweight housing design is optimized for easy and secure insertion, transportation and protection of SIM-sized smart cards and memory.

* For driver download, please visit www.hidglobal.com/omnikey

Specifications

Base Model Number	OMNIKEY® 6221
Dimensions	3.7" x 1.02" x 0.59" / 94 x 26 x 15 mm
Weight	0.6 oz / 17 g
Power supply	USB Powered
Operating temperature	32°-131° F (0° - 55° C)
Operating humidity	10-90% rH
HOST INTERFACE	
Host Interface	USB 2.0 CCID ¹ (also compliant with USB 1.1)
Interface speed	480 Mbps (USB 2.0 High Speed)
SMART CARD INTERFACE	
Standards	Compliant with ISO 7816 and EMV ² 2000 Level 1
Protocols	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I ² C (S=8)
Card size	ID-000 (SIM-size)
Smart Card interface speed	420 kbps (When Supported by Card)
Smart Card clock frequency	Up to 8 MHz
Supported card types	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C
Power to Smart Card	60 mA
Smart Card detection	Movement Detection with Auto Power-Off / Automatic Detection of Smart Card Type / Short Circuit and Thermal Protection
MicroSD Interface	SD Security Command Support, USB 2.0, Removable Media Compatibility up to 32GB (Windows® XP / 2000 SP3, Mac® OS X, Linux® Multi-Lun Mass Storage Class)
MicroSD Slot	Slot-in
Supported APIs	PC/SC driver (ready for 2.01), CT-API (on top of PC/SC), Synchronous-API (on top of PC/SC), OCF (on top of PC/SC)
PC/SC Driver Support	Windows®: XP (32/64bit), 2000, Server 2003 / 2008 R2, CE 5.0, 6.0 / CE.NET (hardware dependant), Vista (32 bit/64 bit), 7 (32bit/64bit), Mac® OS X: 10.4 (PowerPC / Intel), 10.5 (Intel), Linux®
Embedded Technology	OMNIKEY® Smart@Link Chipset
Status indicator	2 x LED
Color	Grey-Blue
Options	Customer Specific Logo, Label and Colors: Available upon request
Composition	Poly carbonate
Durability	Smart Card Insertions = 10,000 / Removable Media Insertions = 10,000
Meantime between failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ³ , ISO 7816, HBCI ⁴ , USB 2.0 (USB 1.1 compatible), CCID ¹
Safety / Environmental	CE, FCC, UL, RoHS
Warranty	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device, 2 = Europay® MasterCard® Visa®, 3 = Windows® Hardware Quality Lab, 4 = Homebanking Computer Interface



© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2010

MKT-OMNIKEY_6221_DS-EN

hidglobal.com



ACCESS experience.

HID Global Offices:

Corporate North America
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Tel: 1 800 237 7769
Tel: +1 949 598 1600
Fax: +1 949 598 1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Tel: +852 3160 9800
Fax: +852 3160 4809

Latin America
Circunvalación Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Haverhill Business Park
Phoenix Road
Haverhill, Suffolk
CB9 7AE
England
Tel: +44 1440 714 850
Fax: +44 1440 714 840